



Amphenol Automotive

Amphenol-Tuchel Electronics GmbH



8mm Female Receptacle 3way

C390 3M03 XH22 400X



PRODUCT CHARACTERISTICS

Mating design	<ul style="list-style-type: none"> - Mounted in e.g. gear box housing - Mating connector for an Amphenol part n°C390 3I03 XH22 20XX
Terminal system	<ul style="list-style-type: none"> - 3 x Ø 8.0mm RADSOK® contact system; silver plated - 2 x 1.2mm HVIL contact system for jumper; silver plated
Termination technology	<ul style="list-style-type: none"> - Press-in
General features	<ul style="list-style-type: none"> - Screw application for further connection - Five codings available

CONSTRUCTION

Housing material	PA, PBT
Contact material	Copper

PERFORMANCE CHARACTERISTICS

Vibration class	V3 (acc. to USCAR 2 Rev. 06)
Current profile (85°C)	230A with 10mm ²
Current profile (105°C)	200A with 10mm ²
Current profile (125°C)	160A with 10mm ²
Voltage range	Max. 800V
Temperature range	-40°C to +125°C

CORRESPONDING CONNECTOR

C390 3I03 XH22 20XX
Ø 8.0mm pin, silver plated
power contact pitch 20,38mm